

DISCHARGE PORTS CHARACTERISTICS OF T.M.O.

	ISKENDERUN (BERTH OF LIMAK)
BERTH LENGTH	370 m
BERTH WIDTH	
SEA WATER DRAFT	14,7 m
DAILY UNLOADING RATE IN BULK (MTON/DAY)	FOR THE VSL(S) LOADED B/L QUANTITY
	BARLEY 0 - 5.250 MT : 3.800 MTON/DAY 5.251 - 10.500 MT : 4.250 MTON/DAY 10.501 - and over MT : 4.250 MTON/DAY

DISCHARGE PORTS CHARACTERISTICS OF T.M.O.
--

	<i>DERINCE</i>
BERTH LENGTH	275 m
BERTH WIDTH	13 m
SEA WATER DRAFT	14,5 m
	UNLOADING BOOM HORIZONTAL LENGTH:Max: 25 m - Min: 16 m
	UNLOADING BOOM VERTICAL LENGTH:Max: 29 m - Min: 20 m
	FOR THE VSL(S) WITH B/L QUANTITY
DAILY UNLOADING RATE IN BULK (MTON/DAY)	BARLEY 0 - 5.250 MT : 2.500 MTON/DAY 5.251 - 10.500 MT : 3.000 MTON/DAY 10.501 - 26.250 MT : 4.500 MTON/DAY 26.251 - 52.500 MT : 6.500 MTON/DAY

DISCHARGE PORTS CHARACTERISTICS OF T.M.O.
--

	Sakarya Karasu Port
BERTH LENGTH	244 m
BERTH WIDTH	20 m
SEA WATER DRAFT	9,5 m
	UNLOADING BOOM HORIZONTAL LENGTH:Max: - Min: -
	UNLOADING BOOM VERTICAL LENGTH:Max: - Min: -
	FOR THE VSL(S) WITH B/L QUANTITY
	BARLEY
DAILY UNLOADING RATE IN BULK (MTON/DAY)	0 - 5.000 MT : 1.000 MTON/DAY 5.001 - 10.000 MT : 1.500 MTON/DAY 10.001 - 20.000 MT : 2.000 MTON/DAY 20.001 - 26.250 MT : 2.500 MTON/DAY

DISCHARGE PORT CHARACTERISTICS OF T.M.O.

	<i>MERSIN (MIP)</i>
BERTH LENGTH	270-490 m
BERTH WIDTH	
SEA WATER DRAFT	9,5-12 m
DAILY UNLOADING RATE IN BULK (MTON/DAY)	FOR THE VSL(S) WITH B/L QUANTITY
	BARLEY 0 - 5.250 MT : 4.000 MTON/DAY 5.251 - 10.500 MT : 5.000 MTON/DAY 10.501 - 26.250 MT : 5.000 MTON/DAY 26.251- 52.500 MT : 5.000 MTON/DAY 52.501 - and over MT: 5.000 MTON/DAY

DISCHARGE PORT CHARACTERISTICS OF T.M.O.

	<i>IZMIR (NEW SILO)</i>
BERTH LENGTH	145 m
BERTH WIDTH	29,7
SEA WATER DRAFT	10 m
	UNLOADING BOOM HORIZONTAL LENGTH: 19.3 m
	UNLOADING BOOM VERTICAL LENGTH: 20 m
	FOR THE VSL(S) WITH B/L QUANTITY
	BARLEY
DAILY UNLOADING RATE IN BULK (MTON/DAY)	0 - 5.250 MT : 2.000 MTON/DAY
	5.251 - 10.500 MT : 2.000 MTON/DAY
	10.501 - 26.250 MT : 3.000 MTON/DAY

DISCHARGE PORT CHARACTERISTICS OF T.M.O.

	BANDIRMA
BERTH LENGTH	180 m
BERTH WIDTH	11 m
SEA WATER DRAFT	9,2 m
	UNLOADING BOOM HORIZONTAL LENGTH:Max: 21 m - Min: 11 m
	UNLOADING BOOM VERTICAL LENGTH:Max: 20,5 m - Min: 9 m
	FOR THE VSL(S) WITH B/L QUANTITY
DAILY UNLOADING RATE IN BULK (MTON/DAY)	<p>BARLEY</p> <p>0 - 5.250 MT : 3.700 MTON/DAY</p> <p>5.251 - 10.500 MT : 3.900 MTON/DAY</p> <p>10.501 - 26.250 MT : 4.000 MTON/DAY</p>

DISCHARGE PORT CHARACTERISTICS OF T.M.O.

	TEKIRDAG (CEYPORT)
BERTH LENGTH	122-423 m
BERTH WIDTH	-
SEA WATER DRAFT	7-11,1 m
DAILY UNLOADING RATE IN BULK (MTON/DAY)	FOR THE VSL(S) WITH B/L QUANTITY
	BARLEY 0 - 5.250 MT: 3.500 MTON/DAY 5.251 - 10.500 MT: 4.000 MTON/DAY 10.501 - 26.250 MT: 4.500 MTON/DAY 26.251 - and over MT: 5.500 MTON/DAY

DISCHARGE PORT CHARACTERISTICS OF T.M.O.

	SAMSUN
BERTH LENGTH	400 - 1.756 m
BERTH WIDTH	50 m
SEA WATER DRAFT	9,5 -10,3 m
	UNLOADING BOOM HORIZONTAL LENGTH: Max: 47 m Min: -
	UNLOADING BOOM VERTICAL LENGTH : Max: 55 m Min: -
	FOR THE VSL(S) WITH B/L QUANTITY
	BARLEY
DAILY UNLOADING RATE IN BULK (MTON/DAY)	0 - 5.250 MT: 2.500 MTON/DAY 5.251 - 10.500 MT: 3.000 MTON/DAY 10.501 - 26.250 MT: 3.000 MTON/DAY

DISCHARGE PORT CHARACTERISTICS OF T.M.O.

	TRABZON
BERTH LENGTH	120 m
BERTH WIDTH	10 m
SEA WATER DRAFT	9 m
	UNLOADING BOOM HORIZONTAL LENGTH: Max: 20 m - Min:12 m
	UNLOADING BOOM VERTICAL LENGTH: Max: 25 m - Min:10 m
	FOR THE VSL(S) WITH B/L QUANTITY
	BARLEY
DAILY UNLOADING RATE IN BULK (MTON/DAY)	0 - 5.250 MT : 1.500 MTON/DAY 5.251 MT and over : 1.500 MTON/DAY